# Fischer Panda® 5000 AC Marine Generator

The Fischer Panda 5000 AC (50Hz) features a twincylinder Kubota Diesel engine for longevity and reliability.

Fischer Panda Generators are the ideal choice for the professional sailor or power boater. When space is tight, weight is critical or noise is an issue, many boaters choose Fischer Panda. The Fischer Panda 5000 AC (50Hz) marine generator is powered by the reliable freshwater-cooled Kubota twin-cylinder diesel engine and our superior asynchronous water-cooled alternator.

All Fischer Panda generators come standard with 100% freshwater cooling, superior sound enclosure, bulkhead external connections, remote fuel lift pump and remotecontrol panel.

Depending upon the kilowatt size Fischer Panda Generators can weigh up to 50% less than a conventional generator and are up to 30% smaller in size.









SMALL

QI

351 S. Andrews Ave., Pompano Beach, FL 33069

Call (800) 508-6494

Visit us at www.fischerpanda.com
or e-mail us at sales@fischerpanda.com




### **FEATURES INCLUDE:**

- Less weight, size and noise
- Extremely quiet (54dba@7meter)
- Direct driven fresh water-cooled Asynchronous Alternator
- Robust twin-cylinder Kubota diesel engine
- VCS electronic governor provides excellent voltage stability
- Integrated internal booster enabling high inductive load starting
- Gear driven raw water pump
- Safety shutdowns for all critical functions
- Self-protected against overload
- Ignition protection for gas powered boats
- Comes complete with harnesses, remote-control panel, sound enclosure and remote fuel lift pump
- 5 Year limited warranty

Fischer Panda <sup>®</sup> 5000 AC Specifications (50Hz)	
Frequency (Hz)	50
Voltage (V)	230
Current Max. (Amp)	21
Peak Output (kW)	4.8
Continuous Output (kW)	4.2
Engine Type	Kubota/Z482
Cylinder/Hp	2 cyl/13.3
Displacement	479 ccm/21.23 cu. in.
Cooling	Heat Exchanger
Noise Level dBa @ 7 meters	54
Length Inches	21.25
Width Inches	17.5
Height Inches	21.9
Weight (Wet) lbs.	268

Rev. 01/15/2025. Fischer Panda Generator is standard with a sound shield.

## Remote Panel



# **OPTIONAL ACCESSORIES**

#### **External Soft Motor Mounts**

External Soft Motor Mounts for extra smooth operation.



#### **Vented Loop**

(anti-siphon valve) Recommended for all installations. Prevents water from siphoning back to the engine and minimizes potential electrolysis. Made with a stainless-steel tube and nylon valve for long life and easy service.



#### **Gas Separator**


Exhaust water separator provides very low back pressure and extra quiet exhaust noise.




#### **Low Profile Muffler**

Low inlet muffler for installations where the muffler cannot be installed lower than the genset.









351 S. Andrews Ave., Pompano Beach, FL 33069

Call (800) 508-6494

Visit us at www.fischerpanda.com or e-mail us at sales@fischerpanda.com

